

View Online at <https://aerobasegroup.com/nsn/5930-00-759-5126>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Dustproof

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.000 inches

**Body Length:**

1.810 inches

**Body Width:**

0.640 inches

**Body Height:**

1.130 inches

**Unthreaded Mounting Hole Diameter:**

0.145 inches

**Actuator Length:**

1.880 inches

**Actuator Style:**

Roller arm

**Actuator Free Position Height:**

0.718 inches

**Actuator Roller Diameter:**

0.380 inches

**Actuator Roller Width:**

0.160 inches

**Maximum Voltage Rating In Volts:**

250.0 ac

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Features Provided:**

Actuator seal

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

1.0 ounces

**Switch Actuating Force:**

6.0 ounces

**Actuator Movement:**

0.250 pretravel inches and 0.187 overtravel inches and 0.062 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

15.000 amperes resistive ac

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0