# NSN 5930-00-759-5126

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-759-5126

# Body Style:

Hole mounted

#### Hazardous Locations/environmental Protection:

Dustproof

## Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

#### Body Length:

1.810 inches

#### **Body Width:**

0.640 inches

#### **Body Height:**

1.130 inches

#### **Unthreaded Mounting Hole Diameter:**

0.145 inches

#### Actuator Length:

1.880 inches

### Actuator Style:

Roller arm

# Actuator Free Position Height:

0.718 inches

## Actuator Roller Diameter:

0.380 inches

#### Actuator Roller Width:

0.160 inches

#### Maximum Voltage Rating In Volts:

250.0 ac

#### Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Unthreaded hole

#### **Features Provided:**

Actuator seal

#### Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

#### Switch Release Force:

1.0 ounces

#### Switch Actuating Force:

6.0 ounces

#### **Actuator Movement:**

 $0.250\ pretravel$  inches and  $0.187\ overtravel$  inches and  $0.062\ differential$  inches

# Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive ac

# NSN 5930-00-759-5126

Sensitive Switch - Page 2 of 2

# Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0

