

View Online at <https://aerobasegroup.com/nsn/5930-00-759-8239>

**Body Style:**

Hole mounted

**Body Length:**

1.250 inches

**Body Width:**

0.750 inches

**Body Height:**

1.460 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.120 inches and 0.130 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

1.212 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.800 inches

**Actuator Width:**

0.050 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained and center position maintained

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Uninclosed

**Mounting Method:**

Bracket and unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, three positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

250.000 milliamperes resistive dc and 25.000 milliamperes inductive dc and 100.000 milliamperes resistive ac

**Test Data Document:**

81349-mil-s-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

3 tab, solder lug

**Specification Data:**

81349-mil-s-3786/31 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0