

View Online at <https://aerobasegroup.com/nsn/5930-00-759-8421>

Thread Class:

3a single pressure connection

Hazardous Locations/environmental Protection:

Moisture proof

Overall Length:

2.500 inches

Outside Diameter:

0.438 inches single connection

Body Length:

1.500 inches

Overall Diameter:

0.870 inches

Pressure Switch Type:

Gage

Width Across Flats:

0.870 inches

Operating Temperature Rating:

Between 0.0 degrees celsius and 50.0 degrees celsius

Mounting Method:

Clamp

Thready Qty Per Inch (tpi):

20 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

150.00 pounds per square inch

Thread Size:

0.4375 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Sensing Element Burst Pressure:

500.00 pounds per square inch

Terminal Type:

Wire hook

Contact Load Current Rating:

550.0 milliamperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

20.00 actuation point pounds per square inch gage and 16.00 deactuation point pounds per square inch gage and 4.00 differential point pounds per square inch gage

Contact Voltage Rating In Volts:

7.5 dc at sea level single voltage

Pressure Connector Type:

Flared, threaded external single connection

Media For Which Designed:

Liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0