NSN 5930-00-759-9566

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-759-9566

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Submersible
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Body Length:
1.938 inches
Body Width:
0.688 inches
Body Height:
0.815 inches
Unthreaded Mounting Hole Diameter:
0.140 inches
Actuator Style:
Round
Actuator Diameter:
0.280 inches
Actuator Free Position Height:
0.835 inches
Maximum Voltage Rating In Volts:
250.0 ac
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, both positions maintained single switch unit
Switch Release Force:
4.0 ounces
Switch Actuating Force:
Between 6.0 ounces and 9.5 ounces
Actuator Movement:
0.012 pretravel inches and 0.052 overtravel inches
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive ac
Terminal Type And Quantity:
3 tab w/screw
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5930-00-759-9566

Sensitive Switch - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A053a0