

View Online at <https://aerobasegroup.com/nsn/5930-00-760-0878>

**Thread Class:**

2a all threaded stud

**Thread Length:**

0.271 inches all threaded stud and 0.291 inches all threaded stud

**Hazardous Locations/environmental Protection:**

Gastight

**Overall Height:**

Between 0.921 inches and 0.982 inches

**Body Height:**

Between 0.410 inches and 0.451 inches

**Overall Diameter:**

Between 0.559 inches and 0.568 inches

**Tempurature Sensing Element Type:**

Internal sensor

**Mounting Method:**

Threaded stud

**Thready Qty Per Inch (tpi):**

32 all threaded stud

**Contact Action Stimulus:**

Increase

**Thread Size:**

0.164 inches all threaded stud

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally closed, momentary action

**Terminal Type:**

Tab, solder lug

**Contact Load Current Rating:**

1.0 amperes inductive load single voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

155.00 actuation point degrees fahrenheit and 135.00 deactuation point degrees fahrenheit

**Contact Voltage Rating In Volts:**

28.0 dc at sea level single voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Disc

**Test Data Document:**

24236-mil-s-24236 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unc all threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0