

View Online at <https://aerobasegroup.com/nsn/5930-00-760-0879>

Thread Class:

2a all threaded stud

Thread Length:

0.271 inches all threaded stud and 0.291 inches all threaded stud

Hazardous Locations/environmental Protection:

Gastight

Overall Height:

Between 0.921 inches and 0.982 inches

Body Height:

Between 0.410 inches and 0.451 inches

Overall Diameter:

Between 0.559 inches and 0.568 inches

Tempurature Sensing Element Type:

Internal sensor

Mounting Method:

Threaded stud

Thready Qty Per Inch (tpi):

32 all threaded stud

Contact Action Stimulus:

Increase

Thread Size:

0.164 inches all threaded stud

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

1.0 amperes inductive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

100.00 actuation point degrees fahrenheit and 80.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Disc

Test Data Document:

24236-mil-s-24236 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc all threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0