# NSN 5930-00-760-1956

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-760-1956

## **Thread Length:**

0.250 inches single mounting facility

## **Overall Length:**

2.312 inches

# **Overall Height:**

1.000 inches

#### **Overall Width:**

0.938 inches

#### First Flat Length:

0.062 inches single actuator

#### Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

0.375 inches single actuator

#### **Nonturn Device Radius:**

# 0.375 inches at 1: 30 o'clock

# Individual Section Quantity:

2

#### Nonturn Device Type:

Tab at 1: 30 o'clock

#### Switch Contact Basic Design:

Nonpile-up symmetrical

#### Pole Quantity:

1 each section front

#### **Throw Quantity:**

12 each section rear

#### **Mounting Method:**

Threaded bushing single mounting facility

#### **Thread Size:**

0.375 inches single mounting facility

#### Contact Voltage Rating In Volts:

28.0 dc at sea level

## **Rotor Through Connection Quantity:**

1 each section

# Switch Actuator Indexing Position Quantity:

12 single actuator

## Shaft Type:

Round, slotted, parallel flatted single actuator

## **Terminal Type:**

Tab, solder lug

#### **Contact Switching Action:**

Breaks before makes each section rear

# NSN 5930-00-760-1956

Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment: 30.0 degrees single actuator Switch Actuator Stop Device Type: Fixed stop single actuator **Contact Load Current Rating:** 1.0 amperes resistive load ac at sea level **Precious Material And Location:** Contacts silver **Precious Material:** Silver Style Designator: Circular wafer, bushing mount **Thread Series Designator:** Unef single mounting facility Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A052b0