

View Online at <https://aerobasegroup.com/nsn/5930-00-760-3907>

Thread Class:

2b all threaded hole

Inside Diameter:

0.200 inches single connection

Overall Length:

2.219 inches

Outside Diameter:

0.250 inches single connection

Overall Height:

2.781 inches

Overall Width:

1.296 inches

Body Length:

2.219 inches

Body Height:

2.344 inches

Longest Horizontal Distance Between Mounting Centers:

0.687 inches

Shortest Horizontal Distance Between Mounting Centers:

0.343 inches

Longest Vertical Distance Between Mounting Centers:

0.468 inches

Pressure Switch Type:

Gage

Mounting Method:

Base and threaded hole

Features Provided:

Capillary tube end seal connection

Thready Qty Per Inch (tpi):

32 all threaded hole

Contact Action Stimulus:

Increase

Thread Size:

0.138 inches all threaded hole

Mounting Facility Pattern:

Isosceles triangle

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Quick disconnect, male

Contact Load Current Rating:

8.3 amperes resistive load single voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

+7.00/+77.00 actuation point pounds per square inch and +7.00/+77.00 deactuation point pounds per square inch gage

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Stimulus Rating:

7.00 actuation point pounds per square inch gage and 30.00 deactuation point pounds per square inch gage and 23.00 differential point pounds per square inch gage

Contact Voltage Rating In Volts:

230.0 ac at sea level single voltage

Pressure Connector Type:

Swivel nut, inverted flare, threaded external single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Unc all threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0