

View Online at <https://aerobasegroup.com/nsn/5930-00-760-3907>

**Thread Class:**

2b all threaded hole

**Inside Diameter:**

0.200 inches single connection

**Overall Length:**

2.219 inches

**Outside Diameter:**

0.250 inches single connection

**Overall Height:**

2.781 inches

**Overall Width:**

1.296 inches

**Body Length:**

2.219 inches

**Body Height:**

2.344 inches

**Longest Horizontal Distance Between Mounting Centers:**

0.687 inches

**Shortest Horizontal Distance Between Mounting Centers:**

0.343 inches

**Longest Vertical Distance Between Mounting Centers:**

0.468 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Base and threaded hole

**Features Provided:**

Capillary tube end seal connection

**Thready Qty Per Inch (tpi):**

32 all threaded hole

**Contact Action Stimulus:**

Increase

**Thread Size:**

0.138 inches all threaded hole

**Mounting Facility Pattern:**

Isosceles triangle

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Quick disconnect, male

**Contact Load Current Rating:**

8.3 amperes resistive load single voltage

**Contact Adjustability:**

Deactuation point adjustable, preset and actuation point adjustable, preset

**Contact Adjustment Range:**

+7.00/+77.00 actuation point pounds per square inch and +7.00/+77.00 deactuation point pounds per square inch gage

**Contact Adjustment Type:**

External deactuation point screw and external actuation point screw

**Contact Stimulus Rating:**

7.00 actuation point pounds per square inch gage and 30.00 deactuation point pounds per square inch gage and 23.00 differential point pounds per square inch gage

**Contact Voltage Rating In Volts:**

230.0 ac at sea level single voltage

**Pressure Connector Type:**

Swivel nut, inverted flare, threaded external single connection

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular

**Thread Series Designator:**

Unc all threaded hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0