

View Online at <https://aerobasegroup.com/nsn/5930-00-760-5122>

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

4.594 inches

Overall Height:

4.375 inches

Overall Width:

3.750 inches

First Flat Length:

0.938 inches single actuator

Flat Height:

0.281 inches single actuator

Shaft Diameter:

0.375 inches single actuator

Shaft Length:

1.250 inches single actuator

Unthreaded Mounting Hole Diameter:

0.313 inches single mounting facility

Individual Section Quantity:

3

Knob Specification Markings:

04009

Longest Horizontal Distance Between Mounting Centers:

3.813 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section rear

Throw Quantity:

1 each section rear

Mounting Method:

Bracket single mounting facility and unthreaded hole single mounting facility

Features Provided:

Actuator knob

Contact Voltage Rating In Volts:

500.0 ac at sea level

Mounting Facility Pattern:

Two position in-line single mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, flatted, threaded hole single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

25.0 amperes resistive load ac at sea level

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0