NSN 5930-00-760-5122

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-760-5122

Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
4.594 inches
Overall Height:
4.375 inches
Overall Width:
3.750 inches
First Flat Length:
0.938 inches single actuator
Flat Height:
0.281 inches single actuator
Shaft Diameter:
0.375 inches single actuator
Shaft Length:
1.250 inches single actuator
Unthreaded Mounting Hole Diameter:
0.313 inches single mounting facility
Individual Section Quantity:
3
Knob Specificationial Markings:
04009
Longest Horizontal Distance Between Mounting Centers:
3.813 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 each section rear
Throw Quantity:
1 each section rear
Mounting Method:
Bracket single mounting facility and unthreaded hole single mounting facility
Features Provided:
Actuator knob
Contact Voltage Rating In Volts:
500.0 ac at sea level
Mounting Facility Pattern:
Two position in-line single mounting facility
Switch Actuator Indexing Position Quantity:
2 single actuator
Shaft Type:
Round, flatted, threaded hole single actuator

NSN 5930-00-760-5122Rotary Switch - Page 2 of 2



Terminal Type:
• •
Tab w/screw
Contact Switching Action:
Breaks before makes each section rear
Switch Actuator Positioning Increment:
90.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
25.0 amperes resistive load ac at sea level
Style Designator:
Tap, circuit selector
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A052b0