

View Online at <https://aerobasegroup.com/nsn/5930-00-760-5122>

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

4.594 inches

**Overall Height:**

4.375 inches

**Overall Width:**

3.750 inches

**First Flat Length:**

0.938 inches single actuator

**Flat Height:**

0.281 inches single actuator

**Shaft Diameter:**

0.375 inches single actuator

**Shaft Length:**

1.250 inches single actuator

**Unthreaded Mounting Hole Diameter:**

0.313 inches single mounting facility

**Individual Section Quantity:**

3

**Knob Specification Markings:**

04009

**Longest Horizontal Distance Between Mounting Centers:**

3.813 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section rear

**Throw Quantity:**

1 each section rear

**Mounting Method:**

Bracket single mounting facility and unthreaded hole single mounting facility

**Features Provided:**

Actuator knob

**Contact Voltage Rating In Volts:**

500.0 ac at sea level

**Mounting Facility Pattern:**

Two position in-line single mounting facility

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Shaft Type:**

Round, flatted, threaded hole single actuator

**Terminal Type:**

Tab w/screw

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

90.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

25.0 amperes resistive load ac at sea level

**Style Designator:**

Tap, circuit selector

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0