

View Online at <https://aerobasegroup.com/nsn/5930-00-760-7234>

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

5.750 inches

Overall Height:

8.750 inches

Overall Width:

3.719 inches

Body Height:

5.750 inches

Unthreaded Mounting Hole Diameter:

0.312 inches

Capillary Tube Length:

33.562 inches

Longest Horizontal Distance Between Mounting Centers:

4.250 inches

Longest Vertical Distance Between Mounting Centers:

4.250 inches

Temperature Sensing Element Type:

Capillary tube

Mounting Method:

Flange and unthreaded hole

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Tab w/screw

Contact Load Current Rating:

15.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+100.00/+650.00 actuation point degrees fahrenheit and +100.00/+650.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External deactuation point knob with scale and external actuation point knob with scale

Contact Voltage Rating In Volts:

230.0 ac at sea level first voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0