

View Online at <https://aerobasegroup.com/nsn/5930-00-760-7234>

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Length:**

5.750 inches

**Overall Height:**

8.750 inches

**Overall Width:**

3.719 inches

**Body Height:**

5.750 inches

**Unthreaded Mounting Hole Diameter:**

0.312 inches

**Capillary Tube Length:**

33.562 inches

**Longest Horizontal Distance Between Mounting Centers:**

4.250 inches

**Longest Vertical Distance Between Mounting Centers:**

4.250 inches

**Temperature Sensing Element Type:**

Capillary tube

**Mounting Method:**

Flange and unthreaded hole

**Features Provided:**

Electrical access port

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Four position rectangular

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally closed, momentary action

**Terminal Type:**

Tab w/screw

**Contact Load Current Rating:**

15.0 amperes resistive load second voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

+100.00/+650.00 actuation point degrees fahrenheit and +100.00/+650.00 deactuation point degrees fahrenheit

**Contact Adjustment Type:**

External deactuation point knob with scale and external actuation point knob with scale

**Contact Voltage Rating In Volts:**

230.0 ac at sea level first voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0