

View Online at <https://aerobasegroup.com/nsn/5930-00-761-0609>

Thread Class:

2a single mounting facility

Thread Length:

0.250 inches single mounting facility

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

1.000 inches

First Flat Length:

0.060 inches single actuator

Flat Height:

0.030 inches single actuator

Shaft Diameter:

0.125 inches single actuator

Shaft Length:

0.375 inches single actuator

Overall Diameter:

0.500 inches

Individual Section Quantity:

1

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

3 single section rear

Mounting Method:

Threaded bushing w/panel seal single mounting facility

Features Provided:

Metallic inclosure

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

115.0 ac at sea level

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round, slotted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

60.0 degrees single actuator

Contact Load Current Rating:

5.0 amperes resistive load ac at sea level

Style Designator:

Miniature, pin mount

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0