NSN 5930-00-761-3407

Pressure Switch - Page 1 of 2

Unthreaded Mounting Hole Diameter:

Overall Length: 5.500 inches Overall Height: 4.625 inches Overall Width: 5.000 inches

0.203 inches

4.750 inches

1.500 inches



View Online at https://aerobasegroup.com/nsn/5930-00-761-3407

Longest Horizontal Distance Between Mounting Centers:

Longest Vertical Distance Between Mounting Centers:

Pressure Switch Type:
Differential
Mounting Method:
Bracket and unthreaded hole
Thready Qty Per Inch (tpi):
27 all pressure connection
Contact Action Stimulus:
Increase
Thread Size:
0.125 inches all pressure connection
Mounting Facility Pattern:
Four position rectangular
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Connector, receptacle
Contact Load Current Rating:
4.0 amperes resistive load third voltage
Contact Adjustability:
Actuation point adjustable
Contact Adjustment Range:
+0.15/+2.00 actuation point inches of water
Contact Adjustment Type:
External actuation point screw
Contact Stimulus Rating:
0.16 actuation point inches of water
Contact Voltage Rating In Volts:
28.0 dc at sea level third voltage
Media For Which Designed:
Liquid

NSN 5930-00-761-3407

Pressure Switch - Page 2 of 2



Cylindrical

Thread Series Designator:

Nptf all pressure connection

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A048b0