NSN 5930-00-761-4181

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-761-4181 **Thread Class:** 2a **Body Style:** Hole mounted **Overall Length:** 2.094 inches **Overall Height:** 2.622 inches **Overall Width:** 0.520 inches **Body Length:** 1.594 inches **Body Width:** 0.520 inches **Body Height:** 2.090 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 1.812 inches **Actuator Style:** Round **Actuator Diameter:** 0.250 inches **Actuator Height:** 0.500 inches **Actuator Free Position Height:** 0.500 inches **Maximum Voltage Rating In Volts:** 250.0 ac **Inclosure Type:** Uninclosed **Mounting Method:** Threaded hole Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.138 inches **Nonpile-up Contact Arrangement:** 2 pole, double throw, one position momentary single switch unit **Switch Release Force:**

4.0 ounces

Switch Actuating Force:

14.0 ounces

NSN 5930-00-761-4181

Sensitive Switch - Page 2 of 2



Actuator Movement:

Between 0.046 pretravel inches and 0.031 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive ac and 10.000 amperes inductive ac and 6.000 amperes motor ac

Thread Series Designator:

Unc

Terminal Type And Quantity:

6 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0