

View Online at <https://aerobasegroup.com/nsn/5930-00-761-5703>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Fungus resistant

Bushing Length:

0.250 inches

Body Length:

0.515 inches

Body Width:

0.515 inches

Body Height:

0.330 inches

Actuator Style:

Round

Actuator Diameter:

0.188 inches

Actuator Height:

0.370 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 2.500 amperes inductive dc and 1.500 amperes resistive ac

Test Data Document:

81349-mil-dtl-83731 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0