

View Online at <https://aerobasegroup.com/nsn/5930-00-761-5703>

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Fungus resistant

**Bushing Length:**

0.250 inches

**Body Length:**

0.515 inches

**Body Width:**

0.515 inches

**Body Height:**

0.330 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.188 inches

**Actuator Height:**

0.370 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.250 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 2.500 amperes inductive dc and 1.500 amperes resistive ac

**Test Data Document:**

81349-mil-dtl-83731 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 turret

**Shelf Life:**

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0