## NSN 5930-00-761-5950

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-761-5950

**Thread Class:** 

2a single mounting facility

Thread Length:

0.437 inches single mounting facility

**Overall Length:** 

1.967 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.219 inches single actuator

**Shaft Diameter:** 

0.250 inches single actuator

**Shaft Length:** 

0.440 inches single actuator

**Overall Diameter:** 

Between 1.100 inches and 1.306 inches

**Nonturn Device Radius:** 

0.375 inches at 3: 00 o'clock

**Individual Section Quantity:** 

1

**Nonturn Device Type:** 

Tab at 3: 00 o'clock

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

**Pole Quantity:** 

1 single section front

**Throw Quantity:** 

12 single section rear

**Mounting Method:** 

Threaded bushing single mounting facility

**Thread Size:** 

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:** 

28.0 dc at sea level

**Rotor Through Connection Quantity:** 

1 single section

**Switch Actuator Indexing Position Quantity:** 

12 single actuator

**Shaft Type:** 

Round, flatted single actuator

**Terminal Type:** 

Tab, solder lug

## NSN 5930-00-761-5950

Rotary Switch - Page 2 of 2



## **Contact Switching Action:**

Makes before breaks single section rear

**Switch Actuator Positioning Increment:** 

30.0 degrees single actuator

**Contact Load Current Rating:** 

1.0 amperes resistive load dc at sea level

Style Designator:

Tap, circular, bushing mount

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A052b0