

View Online at <https://aerobasegroup.com/nsn/5930-00-761-6779>

**Thread Class:**

2a

**Body Style:**

Bushing/hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.000 inches

**Bushing Length:**

0.380 inches

**Body Length:**

1.810 inches

**Body Width:**

0.640 inches

**Body Height:**

0.640 inches

**Unthreaded Mounting Hole Diameter:**

0.145 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.250 inches

**Actuator Height:**

0.417 inches

**Actuator Free Position Height:**

1.047 inches

**Maximum Voltage Rating In Volts:**

250.0 ac

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing and unthreaded hole

**Thread Size:**

0.375 inches

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally closed, momentary action single switch unit

**Switch Release Force:**

2.0 ounces

**Switch Actuating Force:**

12.0 ounces

**Actuator Movement:**

Between 0.375 pretravel inches and 0.035 overtravel inches and 0.140 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

15.000 amperes resistive ac

**Terminal Type And Quantity:**

2 quick disconnect, male

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0