NSN 5930-00-761-6821

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-761-6821

Threa	ad I	end	ath:
11116	au L	.6111	4111.

0.375 inches single mounting facility

Overall Length:

1.830 inches

Overall Height:

1.380 inches

Overall Width:

1.300 inches

First Flat Length:

0.280 inches single actuator

Flat Height:

0.211 inches single actuator and 0.221 inches single actuator

Shaft Diameter:

0.247 inches single actuator and 0.251 inches single actuator

Shaft Length:

0.750 inches single actuator

Nonturn Device Radius:

0.531 inches at 3: 00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Tab at 3: 00 o'clock

Operating Tempurature Range:

-65.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 single section rear

Throw Quantity:

5 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

300.0 highest ac voltage rating at sea level

Shaft Flat/slot Angular Location:

210.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

5 single actuator

Shaft Type:

Round, flatted single actuator

NSN 5930-00-761-6821Rotary Switch - Page 2 of 2

Fiig: A052b0



Terminal Type:
Tab, solder lug
Contact Switching Action:
Breaks before makes single section rear
Switch Actuator Positioning Increment:
30.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
500.0 milliamperes resistive load dc at sea level
Style Designator:
Circular wafer, bushing mount
Test Data Document:
81349-mil-s-3786/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No