

View Online at <https://aerobasegroup.com/nsn/5930-00-761-7246>

Thread Class:

3a all pressure connection

Thread Length:

0.560 inches all pressure connection

Hazardous Locations/environmental Protection:

Dustproof and explosion proof

Overall Length:

1.750 inches

Overall Height:

4.810 inches

Overall Width:

2.930 inches

Body Height:

3.630 inches

Unthreaded Mounting Hole Diameter:

Between 0.201 inches and 0.209 inches

Distance Between Mounting Facility Centers:

2.190 inches

Pressure Switch Type:

Differential

Operating Temperature Rating:

Between 0.0 degrees celsius and 70.0 degrees celsius

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

24 all pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

200.00 pounds per square inch

Thread Size:

0.312 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Sensing Element Burst Pressure:

2000.00 pounds per square inch

Terminal Type:

Screw

Contact Load Current Rating:

5.0 amperes resistive load single voltage and 2.5 amperes inductive load single voltage and 1.0 amperes lamp load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Flared, threaded external all connections

Media For Which Designed:

Liquid

Style Designator:

Rectangular w/bracket

Thread Series Designator:

Unf all pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0