

View Online at <https://aerobasegroup.com/nsn/5930-00-761-9125>

Thread Class:

2b single mounting facility

Hazardous Locations/environmental Protection:

Moisture proof

Overall Length:

4.312 inches

Overall Height:

4.375 inches

Overall Width:

2.906 inches

First Flat Length:

0.940 inches single actuator

Flat Height:

0.203 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

1.031 inches single actuator

Individual Section Quantity:

3

Longest Horizontal Distance Between Mounting Centers:

2.125 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

3.875 inches single mounting facility

Operating Temperature Range:

-55.0/+100.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical and nonpile-up nonsymmetrical

Pole Quantity:

1 2nd section front

Throw Quantity:

6 3rd section front

Mounting Method:

Bracket single mounting facility and threaded hole single mounting facility

Thready Qty Per Inch (tpi):

24 single mounting facility

Thread Size:

0.190 inches single mounting facility

Contact Voltage Rating In Volts:

50.0 dc at sea level

Rotor Through Connection Quantity:

1 2nd section

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

24 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes 3rd section rear

Switch Actuator Positioning Increment:

15.0 degrees single actuator

Contact Load Current Rating:

500.0 milliamperes resistive load dc at sea level

Style Designator:

Square wafer, panel mount

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0