NSN 5930-00-762-4960

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-762-4960

| Threa | d I | Len | gth: |
|-------|-----|-----|------|
| | | | |

0.745 inches single pressure connection

Overall Length:

2.250 inches

Outside Diameter:

0.125 inches single connection

Body Length:

1.380 inches

Overall Diameter:

1.500 inches

Pressure Switch Type:

Gage

Operating Tempurature Rating:

Between -65.0 degrees fahrenheit and 275.0 degrees fahrenheit

Mounting Method:

Inlet connection

Contact Action Stimulus:

Increase

Proof Pressure:

35.00 pounds per square inch

Thread Size:

0.125 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Sensing Element Burst Pressure:

80.00 pounds per square inch

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

5.0 amperes resistive load single voltage

Contact Adjustability:

Actuation point not adjustable

Contact Stimulus Rating:

5.00 actuation point pounds per square inch gage

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Plain, threaded external single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

NSN 5930-00-762-4960

Pressure Switch - Page 2 of 2



| Ī | hread | Series | Desig | nator: |
|---|-------|---------------|-------|--------|
| | | | | |

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0