NSN 5930-00-763-5716

Code Indicating Wheel Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-763-5716

Thread Class:

2b single mounting facility

Overall Length:

1.700 inches

Overall Height:

1.750 inches

Overall Width:

1.371 inches

Individual Section Quantity:

,

Longest Horizontal Distance Between Mounting Centers:

1.000 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

1.178 inches single mounting facility and 1.188 inches single mounting facility

Operating Tempurature Range:

-65.0/+100.0 degrees celsius

Mounting Method:

Threaded hole single mounting facility

Actuator Type:

Thumbwheel single actuator

Thready Qty Per Inch (tpi):

56 single mounting facility

Thread Size:

0.086 inches single mounting facility

Contact Voltage Rating In Volts:

115.0 ac at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

10 single actuator

Terminal Type:

Turret and printed circuit

Contact Load Current Rating:

125.0 milliamperes resistive load ac at sea level

Readout Indicator Marking:

 $Fmf, \, vmf, \, ropta, \, roptm, \, mrc, \, roem, \, roim, \, spl, \, fta, \, mrc \, single \, section$

Contact Arrangement Truth Table:

Decimal, 1 pole - 10 positions single section

Special Features:

Lamp in end piece

Color:

White single indicator marking

NSN 5930-00-763-5716

Code Indicating Wheel Switch - Page 2 of 2



Precious Material And Location: Stator conductors and terminal surfaces gold Precious Material: Gold Style Designator: Rectangular indicating Thread Series Designator: Unc single mounting facility Shelf Life: N/a Unit Of Measure: --Demilitarization: No

Fiig: A052b0