## NSN 5930-00-763-5716

Code Indicating Wheel Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-763-5716

**Thread Class:** 

2b single mounting facility

**Overall Length:** 

1.700 inches

**Overall Height:** 

1.750 inches

**Overall Width:** 

1.371 inches

**Individual Section Quantity:** 

,

**Longest Horizontal Distance Between Mounting Centers:** 

1.000 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:** 

1.178 inches single mounting facility and 1.188 inches single mounting facility

**Operating Tempurature Range:** 

-65.0/+100.0 degrees celsius

**Mounting Method:** 

Threaded hole single mounting facility

**Actuator Type:** 

Thumbwheel single actuator

Thready Qty Per Inch (tpi):

56 single mounting facility

**Thread Size:** 

0.086 inches single mounting facility

**Contact Voltage Rating In Volts:** 

115.0 ac at sea level

**Mounting Facility Pattern:** 

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:** 

10 single actuator

**Terminal Type:** 

Turret and printed circuit

**Contact Load Current Rating:** 

125.0 milliamperes resistive load ac at sea level

**Readout Indicator Marking:** 

 $Fmf, \, vmf, \, ropta, \, roptm, \, mrc, \, roem, \, roim, \, spl, \, fta, \, mrc \, single \, section$ 

**Contact Arrangement Truth Table:** 

Decimal, 1 pole - 10 positions single section

**Special Features:** 

Lamp in end piece

Color:

White single indicator marking

## NSN 5930-00-763-5716

Code Indicating Wheel Switch - Page 2 of 2



## Precious Material And Location: Stator conductors and terminal surfaces gold Precious Material: Gold Style Designator: Rectangular indicating Thread Series Designator: Unc single mounting facility Shelf Life: N/a Unit Of Measure: --Demilitarization: No

Fiig: A052b0