

View Online at <https://aerobasegroup.com/nsn/5930-00-764-9729>

Hazardous Locations/environmental Protection:

Dustproof and watertight

Switch Actuator Quantity:

1

Actuator Position-action Relationship:

Center position maintained and left position maintained

Maximum Voltage Rating In Volts:

115.0 ac

End Application:

Kidd class ddg, virginia class cgn (41), ticonderoga class cg (47), spruance class dd (963); nimitz class cvn, sturgeon class ssn (637), los angeles class ssn (688), forrestal class cv; radar set, lightweight 3d (an/tps-59); an/uyk- (v) sonar/fire control tactical computer

Inclosure Type:

Fully enclosed

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, three positions maintained single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive ac and 3.000 amperes inductive ac

Special Features:

Flexible insulator at terminal end and 0.072 in. W by 0.038 in. Deep keyway in bushing; weapon system essential

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0