## NSN 5930-00-765-5716

Toggle Switch - Page 1 of 2

N/a



View Online at https://aerobasegroup.com/nsn/5930-00-765-5716

| 3 F   |
|---|
| Body Style:   |
| Bushing mount   |
| Hazardous Locations/environmental Protection:   |
| Submersible   |
| Overall Length:   |
| 1.336 inches  |
| Overall Height:   |
| 2.525 inches  |
| Overall Width:  |
| 1.686 inches  |
| Bushing Length:   |
| Between 0.458 inches and 0.478 inches   |
| Body Length:  |
| 1.336 inches  |
| Body Width:   |
| 1.686 inches  |
| Actuator Style:   |
| Round   |
| Actuator Diameter:  |
| Between 0.237 inches and 0.243 inches   |
| Actuator Height:  |
| Between 0.655 inches and 0.719 inches   |
| Maximum Voltage Rating In Volts:  |
| 115.0 ac and 28.0 dc  |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Method:  |
| Threaded bushing  |
| Thready Qty Per Inch (tpi):   |
| 32  |
| Thread Size:  |
| 0.469 inches  |
| Nonpile-up Contact Arrangement:   |
| 4 pole, single throw, both positions maintained single switch unit  |
| Contact Load Current Rating At Maximum Rated Voltage:   |
| $25.000 \ amperes \ resistive \ dc \ and \ 15.000 \ amperes \ inductive \ dc \ and \ 7.000 \ amperes \ lamp \ dc \ and \ 20.000 \ amperes \ resistive \ ac \ and \ 15.000 \ amperes \ and \ 20.000 \ amperes \ resistive \ ac \ and \ 20.000 \ amperes \ ac \ ac \ and \ 20.000 \ amperes \ ac \ a$ |
| amperes inductive ac and 7.000 amperes lamp ac  |
| Thread Series Designator:   |
| Uns   |
| Terminal Type And Quantity:   |
| 8 screw   |
| Shelf Life:   |

## **NSN 5930-00-765-5716**Toggle Switch - Page 2 of 2



|  | Of |  |  |  |
|--|----|--|--|--|

Demilitarization:

No

Fiig:

A053a0