

View Online at <https://aerobasegroup.com/nsn/5930-00-765-6398>

Body Style:

Bushing mounted

Overall Length:

1.680 inches

Overall Height:

0.870 inches

Overall Width:

0.870 inches

Body Diameter:

Between 0.630 inches and 0.670 inches

Bushing Length:

Between 0.290 inches and 0.330 inches

Body Length:

Between 0.760 inches and 0.800 inches

Case Material:

Metal

Actuator Style:

Round

Actuator Diameter:

Between 0.355 inches and 0.395 inches

Actuator Height:

Between 0.230 inches and 0.270 inches

Actuator Color:

Black single actuator

Maximum Voltage Rating In Volts:

120.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.500 inches

Nonpile-up Contact Arrangement:

2 two circuit, double break/double make, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 2.000 amperes inductive dc and 2.000 amperes lamp dc and 4.000 amperes resistive ac and 2.000 amperes inductive ac and 2.000 amperes lamp ac

Test Data Document:

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical" "average" "" etc.)

Thread Series Designator:

Un

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0