

View Online at <https://aerobasegroup.com/nsn/5930-00-766-8551>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Watertight

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.562 inches

**Body Length:**

1.750 inches

**Body Width:**

0.546 inches

**Body Height:**

0.905 inches

**Unthreaded Mounting Hole Diameter:**

0.114 inches

**Actuator Length:**

0.250 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.140 inches

**Actuator Width:**

0.375 inches

**Actuator Free Position Height:**

0.160 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Switch Actuating Force:**

51.0 ounces

**Actuator Movement:**

0.093 pretravel inches and 0.015 overtravel inches and 0.065 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

40.000 amperes resistive dc and 30.000 amperes inductive dc and 15.000 amperes motor dc and 30.000 amperes resistive ac and 20.000 amperes inductive ac and 10.000 amperes motor ac

**Test Data Document:**

81349-mil-s-6743 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

4 tab w/screw

**Specification Data:**

96906-ms25357 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0