

View Online at <https://aerobasegroup.com/nsn/5930-00-766-8551>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Watertight

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.562 inches

Body Length:

1.750 inches

Body Width:

0.546 inches

Body Height:

0.905 inches

Unthreaded Mounting Hole Diameter:

0.114 inches

Actuator Length:

0.250 inches

Actuator Style:

Rectangular

Actuator Height:

0.140 inches

Actuator Width:

0.375 inches

Actuator Free Position Height:

0.160 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Switch Actuating Force:

51.0 ounces

Actuator Movement:

0.093 pretravel inches and 0.015 overtravel inches and 0.065 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

40.000 amperes resistive dc and 30.000 amperes inductive dc and 15.000 amperes motor dc and 30.000 amperes resistive ac and 20.000 amperes inductive ac and 10.000 amperes motor ac

Test Data Document:

81349-mil-s-6743 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

4 tab w/screw

Specification Data:

96906-ms25357 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0