## NSN 5930-00-766-8826

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-766-8826 **Body Style:** Hole mounted **Actuator Style:** Round **Actuator Diameter:** 0.190 inches **Actuator Height:** Between 0.375 inches and 0.380 inches **Actuator Free Position Height:** Between 0.375 inches and 0.380 inches **Housing Height:** 2.000 inches **Housing Length:** 2.060 inches **Housing Width:** 1.340 inches **Center To Center Distance Between Housing Mounting Facilities Parallel To Length:** 1.682 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Width: 1.610 inches **Maximum Voltage Rating In Volts:** 28.0 dc **Inclosure Type:** Hermetically sealed **Mounting Method:** Threaded hole **Nonpile-up Contact Arrangement:** 2 pole, double throw, one position momentary single switch unit **Switch Actuating Force:** 112.0 inch-ounces **Actuator Movement:** 11.0 pretravel degrees and 35.0 overtravel degrees and 7.0 differential degrees **Contact Load Current Rating At Maximum Rated Voltage:** 25.000 amperes resistive dc **Terminal Type And Quantity:** 6 wire lead Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

No

## NSN 5930-00-766-8826

Sensitive Switch - Page 2 of 2



Fiig:

A053a0