

View Online at <https://aerobasegroup.com/nsn/5930-00-766-8832>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.373 inches and 0.377 inches

Body Length:

Between 0.771 inches and 0.791 inches

Body Width:

Between 0.240 inches and 0.260 inches

Body Height:

Between 0.349 inches and 0.369 inches

Unthreaded Mounting Hole Diameter:

Between 0.087 inches and 0.090 inches

Actuator Length:

0.750 inches

Actuator Style:

Leaf

Actuator Width:

0.135 inches

Actuator Free Position Height:

0.254 inches

Maximum Voltage Rating In Volts:

30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

1.0 ounces

Switch Actuating Force:

6.0 ounces

Actuator Movement:

Between 0.155 pretravel inches and 0.030 overtravel inches and 0.010 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 2.500 amperes inductive dc

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0