

View Online at <https://aerobasegroup.com/nsn/5930-00-766-9379>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.375 inches

**Body Length:**

0.789 inches

**Body Width:**

0.250 inches

**Body Height:**

0.665 inches

**Unthreaded Mounting Hole Diameter:**

0.090 inches

**Actuator Length:**

0.296 inches

**Actuator Style:**

Leaf

**Actuator Width:**

0.062 inches

**Actuator Free Position Height:**

0.360 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Hermetically sealed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

1.0 ounces

**Switch Actuating Force:**

7.0 ounces

**Actuator Movement:**

Between 0.030 pretravel inches and 0.003 overtravel inches and 0.006 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac and 3.000 amperes inductive ac

**Terminal Type And Quantity:**

3 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0