NSN 5930-00-766-9379

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-766-9379 **Body Style:** Hole mounted **Center To Center Distance Between Mounting Facilities Parallel To Length:** 0.375 inches **Body Length:** 0.789 inches **Body Width:** 0.250 inches **Body Height:** 0.665 inches **Unthreaded Mounting Hole Diameter:** 0.090 inches **Actuator Length:** 0.296 inches **Actuator Style:** Leaf **Actuator Width:** 0.062 inches **Actuator Free Position Height:** 0.360 inches **Maximum Voltage Rating In Volts:** 115.0 ac and 28.0 dc **Inclosure Type:** Hermetically sealed **Mounting Method:** Unthreaded hole **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary single switch unit **Switch Release Force:** 1.0 ounces **Switch Actuating Force:** 7.0 ounces **Actuator Movement:** Between 0.030 pretravel inches and 0.003 overtravel inches and 0.006 differential inches **Contact Load Current Rating At Maximum Rated Voltage:** 5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac and 3.000 amperes inductive ac **Terminal Type And Quantity:** 3 wire lead Shelf Life: N/a

--

Unit Of Measure:

NSN 5930-00-766-9379

Sensitive Switch - Page 2 of 2



em			

No

Fiig:

A053a0