

View Online at <https://aerobasegroup.com/nsn/5930-00-770-8420>

Thread Class:

2a single mounting facility

Thread Length:

0.312 inches single mounting facility

Overall Length:

1.531 inches

Overall Height:

1.438 inches

Overall Width:

1.000 inches

First Flat Length:

0.406 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.531 inches single actuator

Individual Section Quantity:

1

Nonturn Device Type:

Slotted bushing at 6: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

3 single section front

Throw Quantity:

4 single section front

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

500.0 highest ac voltage rating at sea level

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, v flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks single section front

Switch Actuator Positioning Increment:

20.0 degrees single actuator

Contact Load Current Rating:

1.0 amperes resistive load lowest ac voltage rating at sea level

Style Designator:

Tap, circular frame

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0