

View Online at <https://aerobasegroup.com/nsn/5930-00-772-3954>

Overall Length:

4.500 inches

Outside Diameter:

0.250 inches single connection

Body Diameter:

3.500 inches

Mounting Slot Width:

Between 0.195 inches and 0.200 inches

Unthreaded Mounting Hole Diameter:

Between 0.195 inches and 0.200 inches

Longest Horizontal Distance Between Mounting Centers:

3.000 inches

Longest Vertical Distance Between Mounting Centers:

0.625 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket and unthreaded hole and slot

Features Provided:

Electrical box connector

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

1.0 amperes inductive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

69.00 actuation point pounds per square inch and 57.00 deactuation point pounds per square inch and 12.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Beveled, butt weld single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical w/mounting lugs

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0