

View Online at <https://aerobasegroup.com/nsn/5930-00-772-3954>

**Overall Length:**

4.500 inches

**Outside Diameter:**

0.250 inches single connection

**Body Diameter:**

3.500 inches

**Mounting Slot Width:**

Between 0.195 inches and 0.200 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.195 inches and 0.200 inches

**Longest Horizontal Distance Between Mounting Centers:**

3.000 inches

**Longest Vertical Distance Between Mounting Centers:**

0.625 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Bracket and unthreaded hole and slot

**Features Provided:**

Electrical box connector

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Four position rectangular

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action

**Terminal Type:**

Connector, receptacle

**Contact Load Current Rating:**

1.0 amperes inductive load single voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

69.00 actuation point pounds per square inch and 57.00 deactuation point pounds per square inch and 12.00 differential point pounds per square inch

**Contact Voltage Rating In Volts:**

28.0 dc at sea level single voltage

**Pressure Connector Type:**

Beveled, butt weld single connection

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Cylindrical w/mounting lugs

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0