

View Online at <https://aerobasegroup.com/nsn/5930-00-772-9276>

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Submersible

**Overall Length:**

1.336 inches

**Overall Height:**

2.400 inches

**Overall Width:**

0.734 inches

**Bushing Length:**

Between 0.458 inches and 0.478 inches

**Body Length:**

1.336 inches

**Body Width:**

0.734 inches

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.237 inches and 0.243 inches

**Actuator Height:**

Between 0.655 inches and 0.719 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**End Application:**

Missile minuteman Igm-30

**Mounting Surface To Terminal End Distance:**

1.250 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

25.000 amperes resistive dc and 15.000 amperes inductive dc and 7.000 amperes lamp dc and 20.000 amperes resistive ac and 15.000 amperes inductive ac and 7.000 amperes lamp ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

3 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0