NSN 5930-00-773-0276

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-773-0276

| Body Style: Hole mounted Hazardous Locations/environmental Protection: Dustproof Center To Center Distance Between Mounting Facilities Parallel To Length: 1.000 inches Body Length: 1.940 inches Body Width: 0.687 inches Body Height: |
|--|
| Hazardous Locations/environmental Protection: Dustproof Center To Center Distance Between Mounting Facilities Parallel To Length: 1.000 inches Body Length: 1.940 inches Body Width: 0.687 inches |
| Dustproof Center To Center Distance Between Mounting Facilities Parallel To Length: 1.000 inches Body Length: 1.940 inches Body Width: 0.687 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: 1.000 inches Body Length: 1.940 inches Body Width: 0.687 inches |
| 1.000 inches Body Length: 1.940 inches Body Width: 0.687 inches |
| Body Length: 1.940 inches Body Width: 0.687 inches |
| 1.940 inches Body Width: 0.687 inches |
| Body Width: 0.687 inches |
| 0.687 inches |
| |
| Body Height: |
| |
| 1.040 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.152 inches |
| Actuator Style: |
| Leaf |
| Actuator Width: |
| 0.190 inches |
| Actuator Free Position Height: |
| 0.750 inches |
| Maximum Voltage Rating In Volts: |
| 460.0 ac and 250.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Unthreaded hole |
| Nonpile-up Contact Arrangement: |
| 1 pole, double throw, both positions maintained single switch unit |
| Switch Release Force: |
| 1.0 ounces |
| Switch Actuating Force: |
| 6.0 ounces |
| Actuator Movement: |
| Between 0.218 pretravel inches and 0.218 overtravel inches and 0.004 differential inches |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 250.000 milliamperes resistive dc and 15.000 amperes resistive ac |
| Terminal Type And Quantity: |
| 3 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5930-00-773-0276

Sensitive Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A053a0