

View Online at <https://aerobasegroup.com/nsn/5930-00-773-3445>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Flame resistant

Overall Length:

1.687 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.497 inches and 0.503 inches

Overall Height:

1.015 inches

Overall Width:

0.515 inches

Body Length:

Between 1.235 inches and 1.265 inches

Body Width:

0.515 inches

Body Height:

0.890 inches

Unthreaded Mounting Hole Diameter:

Between 0.114 inches and 0.116 inches

Actuator Length:

Between 0.235 inches and 0.265 inches

Actuator Style:

Rectangular

Actuator Height:

0.125 inches

Actuator Width:

Between 0.281 inches and 0.311 inches

Actuator Free Position Height:

Between 0.495 inches and 0.515 inches

Actuator Adapter Style:

Pushbutton

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Uninclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

2 two circuit, double break/double make, one position momentary single switch unit

Switch Actuating Force:

34.8 ounces

Actuator Movement:

Between 0.060 pretravel inches and 0.015 overtravel inches and 0.035 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive dc and 10.000 amperes inductive dc and 10.000 amperes motor dc and 15.000 amperes resistive ac and 15.000 amperes inductive ac and 6.000 amperes motor ac

Test Data Document:

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

8 tab, solder lug

Specification Data:

81349-mil-s-8805/15 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0