

View Online at <https://aerobasegroup.com/nsn/5930-00-773-6452>

Thread Class:

2a

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Watertight

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.875 inches

Body Length:

1.070 inches

Body Width:

0.840 inches

Body Height:

0.720 inches

Unthreaded Mounting Hole Diameter:

0.112 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.406 inches

Actuator Length:

0.810 inches

Actuator Style:

Roller arm

Actuator Free Position Height:

0.806 inches

Actuator Roller Diameter:

0.190 inches

Actuator Roller Width:

0.190 inches

Maximum Voltage Rating In Volts:

250.0 ac and 125.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded hole

Thready Qty Per Inch (tpi):

40

Thread Size:

0.112 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Switch Release Force:

2.0 ounces

Switch Actuating Force:

30.0 ounces

Actuator Movement:

Between 0.078 pretravel inches and 0.031 overtravel inches and 0.040 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

500.000 milliamperes resistive dc and 10.000 amperes resistive ac

Thread Series Designator:

Unc

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0