

View Online at <https://aerobasegroup.com/nsn/5930-00-773-8170>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

1.364 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.875 inches

Overall Height:

0.760 inches

Overall Width:

0.400 inches

Body Length:

1.094 inches

Body Width:

0.400 inches

Body Height:

0.625 inches

Unthreaded Mounting Hole Diameter:

0.114 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.406 inches

Actuator Style:

Roller plunger

Actuator Free Position Height:

0.590 inches

Actuator Roller Diameter:

0.190 inches

Actuator Roller Width:

0.190 inches

Actuator Adapter Style:

Roller leaf

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded hole

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

40

Thread Size:

0.112 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

Between 6.0 ounces and 14.0 ounces

Contact Load Current Rating At Maximum Rated Voltage:

6.000 amperes resistive dc and 10.000 amperes motor dc and 10.000 amperes resistive ac

Thread Series Designator:

Unc

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0