

View Online at <https://aerobasegroup.com/nsn/5930-00-774-5541>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.240 inches single mounting facility and 0.260 inches single mounting facility

**Overall Length:**

Between 2.710 inches and 2.730 inches

**First Flat Length:**

0.275 inches single actuator

**Flat Height:**

0.218 inches single actuator

**Shaft Diameter:**

0.270 inches single actuator and 0.280 inches single actuator

**Shaft Length:**

0.930 inches single actuator and 0.970 inches single actuator

**Overall Diameter:**

Between 1.000 inches and 1.010 inches

**Nonturn Device Radius:**

0.437 inches at 6:00 o'clock

**Individual Section Quantity:**

3

**Nonturn Device Type:**

Slotted bushing at 6:00 o'clock

**Operating Temperature Range:**

-65.0/+100.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section front

**Throw Quantity:**

2 each section front

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

115.0 ac at sea level

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section front

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

1.0 amperes resistive load ac at sea level

**Precious Material And Location:**

Contacts silver

**Precious Material:**

Silver

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0