NSN 5930-00-774-6486

Rotary Switch - Page 1 of 2

Thread Length:



View Online at https://aerobasegroup.com/nsn/5930-00-774-6486

Overall Length: 1.844 inches Overall Height: 2.312 inches Overall Width: 1.969 inches First Flat Length: 0.562 inches single actuator Flat Height: 0.158 inches single actuator Shaft Diameter: 0.250 inches single actuator Shaft Length: 0.938 inches single actuator Individual Section Quantity: 1 Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 2 single section rear Throw Quantity:					
Overall Height: 2.312 inches Overall Width: 1.969 inches First Flat Length: 0.562 inches single actuator Flat Height: 0.158 inches single actuator Shaft Diameter: 0.250 inches single actuator Shaft Length: 0.938 inches single actuator Individual Section Quantity: 1 Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 2 single section rear					
2.312 inches Overall Width: 1.969 inches First Flat Length: 0.562 inches single actuator Flat Height: 0.158 inches single actuator Shaft Diameter: 0.250 inches single actuator Shaft Length: 0.938 inches single actuator Individual Section Quantity: 1 Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 2 single section rear					
Overall Width: 1.969 inches First Flat Length: 0.562 inches single actuator Flat Height: 0.158 inches single actuator Shaft Diameter: 0.250 inches single actuator Shaft Length: 0.938 inches single actuator Individual Section Quantity: 1 Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 2 single section rear					
1.969 inches First Flat Length: 0.562 inches single actuator Flat Height: 0.158 inches single actuator Shaft Diameter: 0.250 inches single actuator Shaft Length: 0.938 inches single actuator Individual Section Quantity: 1 Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 2 single section rear					
First Flat Length: 0.562 inches single actuator Flat Height: 0.158 inches single actuator Shaft Diameter: 0.250 inches single actuator Shaft Length: 0.938 inches single actuator Individual Section Quantity: 1 Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 2 single section rear					
0.562 inches single actuator Flat Height: 0.158 inches single actuator Shaft Diameter: 0.250 inches single actuator Shaft Length: 0.938 inches single actuator Individual Section Quantity: 1 Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 2 single section rear					
Flat Height: 0.158 inches single actuator Shaft Diameter: 0.250 inches single actuator Shaft Length: 0.938 inches single actuator Individual Section Quantity: 1 Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 2 single section rear					
0.158 inches single actuator Shaft Diameter: 0.250 inches single actuator Shaft Length: 0.938 inches single actuator Individual Section Quantity: 1 Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 2 single section rear					
Shaft Diameter: 0.250 inches single actuator Shaft Length: 0.938 inches single actuator Individual Section Quantity: 1 Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 2 single section rear					
0.250 inches single actuator Shaft Length: 0.938 inches single actuator Individual Section Quantity: 1 Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 2 single section rear					
Shaft Length: 0.938 inches single actuator Individual Section Quantity: 1 Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 2 single section rear					
0.938 inches single actuator Individual Section Quantity: 1 Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 2 single section rear					
Individual Section Quantity: 1 Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 2 single section rear					
Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 2 single section rear					
Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 2 single section rear					
Nonpile-up symmetrical Pole Quantity: 2 single section rear					
Pole Quantity: 2 single section rear					
2 single section rear					
Throw Quantity:					
8 single section rear					
Mounting Method:					
Threaded bushing single mounting facility					
Thread Size:					
0.375 inches single mounting facility					
Contact Voltage Rating In Volts:					
230.0 dc at sea level					
Switch Actuator Indexing Position Quantity:					
8 single actuator					
Shaft Type:					
Round, flatted single actuator					
Terminal Type:					
Tab, solder lug					
Contact Switching Action:					
Breaks before makes single section rear					
Switch Actuator Positioning Increment:					
20.0 degrees single actuator					

Contact Load Current Rating:

250.0 milliamperes resistive load dc at sea level

NSN 5930-00-774-6486

Rotary Switch - Page 2 of 2



T	'nr	ead	Series	Desig	nator
-			-0	-00.9	

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0