NSN 5930-00-775-6059

Rotary Switch - Page 1 of 2

Thread Class:



View Online at https://aerobasegroup.com/nsn/5930-00-775-6059

2a single mounting facility **Thread Length:** 0.375 inches single mounting facility **Overall Length:** 4.000 inches **Overall Height:** 1.531 inches **Overall Width:** 1.312 inches **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 0.500 inches single actuator **Nonturn Device Radius:** 0.531 inches at 2: 00 o'clock **Individual Section Quantity:** 6 **Nonturn Device Type:** Tab at 2: 00 o'clock **Operating Tempurature Range:** -65.0/+85.0 degrees celsius **Switch Contact Basic Design:** Nonpile-up nonsymmetrical **Mounting Method:** Threaded bushing single mounting facility **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 28.0 dc at sea level **Switch Actuator Indexing Position Quantity:** 10 single actuator **Shaft Type:** Round single actuator **Terminal Type:** Tab, solder lug **Switch Actuator Positioning Increment:** 36.0 degrees single actuator

Fixed stop single actuator

Detent Rotational Torque Range:

Switch Actuator Stop Device Type:

+30.000/+100.000 inch-ounces single actuator

NSN 5930-00-775-6059

Rotary Switch - Page 2 of 2



Contact Load Current Rating

1.0 amperes resistive load ac at sea level

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A052b0