NSN 5930-00-775-7512

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-775-7512

Thread Length:
0.250 inches single mounting facility
Overall Length:
4.625 inches
Overall Height:
1.750 inches
Overall Width:
1.750 inches
First Flat Length:
0.375 inches single actuator
Flat Height:
0.216 inches single actuator
Shaft Diameter:
0.250 inches single actuator
Shaft Length:
4.375 inches single actuator
Individual Section Quantity:
3
Operating Tempurature Range:
-55.0/+105.0 degrees celsius
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 single section front
Throw Quantity:
11 single section front
11 single section front Mounting Method:
Mounting Method:
Mounting Method: Threaded bushing single mounting facility
Mounting Method: Threaded bushing single mounting facility Features Provided:
Mounting Method: Threaded bushing single mounting facility Features Provided: Variable resistor
Mounting Method: Threaded bushing single mounting facility Features Provided: Variable resistor Thread Size:
Mounting Method: Threaded bushing single mounting facility Features Provided: Variable resistor Thread Size: 0.375 inches single mounting facility
Mounting Method: Threaded bushing single mounting facility Features Provided: Variable resistor Thread Size: 0.375 inches single mounting facility Switch Actuator Momentary Position:
Mounting Method: Threaded bushing single mounting facility Features Provided: Variable resistor Thread Size: 0.375 inches single mounting facility Switch Actuator Momentary Position: Clockwise single actuator
Mounting Method: Threaded bushing single mounting facility Features Provided: Variable resistor Thread Size: 0.375 inches single mounting facility Switch Actuator Momentary Position: Clockwise single actuator Shaft Flat/slot Angular Location:
Mounting Method: Threaded bushing single mounting facility Features Provided: Variable resistor Thread Size: 0.375 inches single mounting facility Switch Actuator Momentary Position: Clockwise single actuator Shaft Flat/slot Angular Location: 30.0 degrees from nonturn device single actuator
Mounting Method: Threaded bushing single mounting facility Features Provided: Variable resistor Thread Size: 0.375 inches single mounting facility Switch Actuator Momentary Position: Clockwise single actuator Shaft Flat/slot Angular Location: 30.0 degrees from nonturn device single actuator Shaft Type:
Mounting Method: Threaded bushing single mounting facility Features Provided: Variable resistor Thread Size: 0.375 inches single mounting facility Switch Actuator Momentary Position: Clockwise single actuator Shaft Flat/slot Angular Location: 30.0 degrees from nonturn device single actuator Shaft Type: Round, flatted single actuator
Mounting Method: Threaded bushing single mounting facility Features Provided: Variable resistor Thread Size: 0.375 inches single mounting facility Switch Actuator Momentary Position: Clockwise single actuator Shaft Flat/slot Angular Location: 30.0 degrees from nonturn device single actuator Shaft Type: Round, flatted single actuator Terminal Type:

NSN 5930-00-775-7512

Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Style Designator:

Tap, square frame

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0