

View Online at <https://aerobasegroup.com/nsn/5930-00-776-1023>

Thread Class:

2a single mounting facility

Thread Length:

0.410 inches single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

2.265 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.210 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.780 inches single actuator

Overall Diameter:

1.500 inches

Individual Section Quantity:

2

Nonturn Device Type:

Slotted bushing at 12: 00 o'clock

Operating Temperature Range:

-65.0/+125.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

7 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

195.0 degrees from nonturn device single actuator

Rotor Through Connection Quantity:

1 each section

Switch Actuator Indexing Position Quantity:

7 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

22.5 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load ac at sea level and 2.0 amperes inductive load ac at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0